

START 9176968

EXTERNAL CONTROL PANELS

230-400 Vac







APPLICATION

1 actuator for sectional doors and rolling doors, folding doors with more than two sections, unbalanced shutters and industrial sliding

CONTROL PANEL POWER SUPPLY

230 Vac o 400 Vac

MOTORS POWER SUPPLY

230 Vac 900W o 400 Vac 2200W

MAIN FUNCTIONS:

- Dead man functioning logic
- · Fixed terminal blocks
- Motor limit switch inputs
- Open, close and emergency stop inputs
- Open and close buttons built-in to the control unit
- Output for connection of flasher and auxiliary capacitor for motor start inrush

	456 000	789 000	10 11 00		14 15 16 200			22 23 24 25 26	
230 Vac / 50 Hz 400 Vac / 50 Hz		230 Vac 0,2 A	C aux	STOP	SW0 (Open)	SWC (Close)	CLOSE	SAFETY 22 23 12 31 230 Vac 400 Vac 24 25 26 24 25 26	

ACCESSORIES



DA.2S 9760100 Electronic card that allows synchronised movement of 2 automations (facing doors).

SC.RD

9760027

Board no. 4 relays

for control unit inputs

support/decoupling.

For use in the

event of very long

connections (i.e.

buttons in house).



9855001

KPO

Set of 2 green push buttons (N.O.) and front cover for Box LB.



www.beninca.com

VERSIONS



START.I 9176183

START control units with open, close, stop buttons with self-hold and three-pole doorblocking switch incorporated in the control panel. Resistant box for use in industrial environments, degree of protection IP 55.