



BULL424ESA



CONTROL PANELS:

BULL424ESA — CP.B24ESA



AUTOMATIONS FOR SLIDING GATES RESIDENTIAL USE

control with built-in encoder and receiver
personalised release key
up to 450 kg





24 Vdc **intensive use**

- 24 Vdc geared motor for intensive use, with built-in control unit, ESA SYSTEM and encoder
- The encoder device ensures maximum safety and precision in the gate moving phases
- Amperometric sensor obstacle detection system to prevent crushing
- Battery back up system ready
- Full metal release system
- Magnetic limit switches accessory available (MLS)



BULL.P3

Raised foundation plate included.
Floor fixing distance 260 x 117, no. 4 Ø 11,
motor fixing distance 300 x 75 no. 4



■ COMPLETE KITS

KBULL424 9592090

- 1 BULL424ESA 24 Vdc Operator with control panel and built-in receiver. ESA SYSTEM technology included
- 1 PUPILLA.F Pair of photocells
- 1 LAMPI24.LED 24 Vdc Led flashing light with built-in aerial
- 1 TOKEY Metal key selector
- 1 TO.GO2WV 433.92 MHz Transmitter





RI.M4F
9272010

M4 rack 30x12x1000mm slotted and galvanized. Supplied with M6 metric screws and threaded spacers.

Packaging: 4 pcs



RI.M4Z
9272030

M4 galvanized rack (22x22x2000 mm).

Packaging: 2 pcs



RI.M4P
9272020

M4 Nylon rack with steel core, 28x40x1000 mm. Slotted, supplied with self-drilling screws.

Packaging: 10 pcs



MLS
9387001

Magnetic limit switches for BULL. Suitable for snowy places.



SB.BULL8.F
9747025

Externally fitted anti-intrusion cable unlock device (L=4.5m).










ID.TA
9846019

Warning board.



KSUN
9611004

KIT for system operation via solar panel. For 24 Vdc models.



 **MADE IN ITALY**

AUTOMATISMI BENINCA SpA • via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • F +39 0444 759728 • sales@beninca.it

TECHNICAL DATA	BULL424ESA
Code	9591433
Power supply	230 Vac (50-60Hz)
Motor supply	24 Vdc
Max absorbed current	0.4 A
Power consumption in stand-by	8 mA
Max Thrust	428 N
Opening speed	6.7-11 m/min
Operation cycle	intensive use
Protection level	IP44
Operating temperature	-20°C /+50°C
Max gate weight	450 kg
Driving gear for rack	M4 Z14
Weight	10.2 kg
Items no. per pallet	36
Kits no. per pallet	30